Estimating XML Query Cardinality

Carlo Sartiani
Dipartimento di Informatica - Università di Pisa
Presented by
Giorgio Ghelli

Issues in Result Size Estimation

- Twigs
 - branch correlation
- Set cardinality (let ... :=)
- Predicates

The Framework

- Model independent
- It offers
 - correlation
 - group cardinality estimation
 - predicate selectivity application

Basics

- Estimation functions compute the distribution of data into query result
- Result distribution is expressed by means of sequences of match occurrences
- Sequence of match occurrences are bound to variables

Match Occurrence

- @ (I,r,m)
- I: tag of the matching nodes
- r: region of the database
- m: multiplicity of the occurrence

Regions

- Intensional regions: types
- Extensional regions: position intervals, etc
- Mixed regions: intensional + extensional

Tagged Regions


- Regions augmented with tag information
 - @ (l,r)
- Organized into a graph
 - /-edges,//-edges,etc

Correlation

- (I,r,m) and (I',r',m') are correlated wrt to (I",r",m")
- of (l'',r'') is a common ancestor for (l,r) and (l',r') in the tagged region graph

More on Correlation

(title,r1,m1)
correlated to
(author,r2,m2) wrt
(book,r3,m3)?



- Constrained common ancestor problem
- O(n) time complexity (with proper data structures)

Groups

- Estimating the distribution of data into sets created by the let clause
 - Distributing match occurrences into sets
 - Correlation-based

More on Groups

- Number of groups determined by the cardinality of the root variable
- Performed in O(n²) time
- Extensible to future groupby constructs

Predicates

- Predicate selectivity depends on
 - the kind of predicates
 - the semantics of the data being filtered

More on Predicates

- Selectivity factor
 - psf[P]: TaggedRegion -> [0,1]
- Factors propagated to the occurrences of the same twig

Conclusions

- An infrastructure for size estimation models
- Future work
 - groupby
 - more tree-oriented vision